



Acqua fredda
Cold water



Per uso saltuario
For occasional usage



Lancia getto rotante
Rotary lance

TSS[®]
Total Stop
SYSTEM

Caratteristiche Generali - General Features:

- Carrello a 2 ruote completo di manico
- Pompa a 3 pistoni assiali comandati dal plettello oscillante, testa alluminio
- Pistoni in acciaio Inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Sistema di arresto totale dell' idropulitrice a distanza
- Protezione termica del motore
- Aspirazione detergente diretta con serbatoio incorporato
- Capacità del serbatoio detergente 1,4l
- Filtro acqua ispezionabile
- Lunghezza cavo elettrico 5 m
- Two-wheel trolley with handle
- 3 Axial stainless steel pistons wobble-plate pump with aluminium head
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Remote control for total shut-down of high pressure washer
- Motor thermal protector
- Built-in detergent tank for direct suction
- Detergent tank capacity 1.4l
- Inspectable water filter
- Electric cable length 5 m

Fornito con - Equipped with:

Pistola
Trigger gun
(Cod. 3900180)



Lancia con getto rotante
Rotary lance
(Cod. 3900190)



Lancia con getto regolabile
Lance with adjustable spray nozzle
(Cod. 3900100)



Tubo AP 8 m (PU)
HP hose 8 m (PU)
(Cod. 4381510)



Dati Tecnici / Technical Data

MOD	COD	MAX		l/h		rpm		Hz	V	kg
		bar	psi	l/h	gph	kW				
HU145	14358	145	2100	440	116	1,9	3400	1~50	230	12

Temperatura massima acqua / Max inlet water temperature
50°C 122°F IPX5-S1